

Sudspave[®]: porous aggregate surface

Structural design, installation and maintenance guidance

Sudspave is a recycled plastic cellular porous paving solution for use in Sustainable Drainage Systems (SuDS). Sudspave is suitable for a wide range of trafficked applications where a stabilised, free-draining gravel surface is required. Typical applications include: car parks, emergency access, maintenance routes, cycle paths, pedestrian and disabled access. Considerations relating to the movement and attenuation of water within the porous pavement are not covered in this document. This document is intended to be a summary presenting typical solutions. Contact ABG for detailed site specific advice.

Typical construction detail

Sudspave[®] 40

Recycled plastic cellular paver infilled with angular aggregate


Sub-base stabilisation

ABG Abgrid geogrid (typical)

Lower filter/separator geotextile

ABG Terrex NW9 geotextile (typical)

Subgrade



Technical Specification

System	Sudspave 40
Material	100% recycled and recyclable plastic
Colour	Black – other options available on request.
Paving unit dimensions	40mm x 500mm x 500mm.
Coverage rate	4 units per m ² panel – supplied pre-connected. 59m ² per pallet.
Cell dimension	25 round (60mm dia.) & 24 plaque shaped (60x85mm dia) cells each with 2 basal crossbars (60 x 5mm).
Cell structure	Robust diagonally linked semi-flexural lattice of circular and plaque shaped cells.
Paving unit footprint	Open structured with 2 basal load-bearing, reinforcing crossbars per cell.
Paver weight	1.28kg/paving unit & 5.12kg/m ² panel.
Compression strength (filled)	300 tonnes/m ² \cong 3000 kN/m ² (gravel filled).
Permissible axle load	16 tonnes \cong 160kN (gravel filled).
Paver interlock mechanism	Positive self-locking T-shaped lug and clip-slot mechanism. 8 clips per linear metre.
Expansion & contraction	In-built flexural cell design. Range -50 to +70 deg C.
Parking bay & line markers	White mouldings (60mm dia.) slot & lock into round cells. Other colours available.
Chemical resistance	Excellent.
UV stability	High resistance to colour & strength degradation.
Infiltration capacity	Limited only by the permeability of the specified infill, bedding & sub-base materials.
Cell infill material	Porous, clean angular aggregate: 3-14mm particle size, with greater proportion in 7-10mm range, and in accordance with Table A.3 of BS 7533-13.
Bedding layer material	Porous, clean angular aggregate: 3-14mm particle size, with greater proportion in 7-10mm range, and in accordance with Table A.3 of BS 7533-13.
Bedding layer thickness	A level & uniform layer thickness: 10mm - 20mm maximum.
Upper filter/separator geotextile	ABG Terrex NW9 non-woven geotextile : 1.1mm thick : 120g/m ² : zero breakthrough head (optional, Ref. Note F).
Sub-base material	DTp Type 3 or a drained Type 1, or BS 7533-13 4/20 or 4/40 (Ref. Note C).
Sub-base layer thickness	Refer to Table 1 for thickness "D" in millimeters (mm).
Sub-base stabilisation	Typically Abgrid 20/20 or 30/30 geogrid (see Table 1). Alternative options may be suitable (Ref. Note B).
Lower filter/separator geotextile	ABG Terrex NW9 non-woven geotextile : 1.1mm thick : 120g/m ² : zero breakthrough head.

All information is supplied in good faith and without charge to enable reasonable assessment of the practical performance of ABG products. Final determination of the suitability of information or material for the use contemplated and the manner of the use is the sole responsibility of the user. As design and installation is beyond the control of ABG (unless specifically requested) no warranty is given or implied and the information does not form part of any contract. ABG reserve the right to update the information within at any time without prior notice. ©²⁰¹⁴ ABG Ltd

Sudspave Gravel Design, Install and Maintenance Summary TECH NOTE - Rev1.02

abg ltd. E7 Meltham Mills Rd, Meltham, West Yorkshire, HD9 4DS

UK t 01484 852096 e geo@abgltd.com Export t +44(0)1484 852250 e export@abgltd.com

www.abgltd.com

Structural design, installation and maintenance guidance for gravel surfaces

SUDSPAWE® INSTALLATION PROCESS

The following generic guidance must be read in conjunction with the specific project specification within the contract documents

1. Install the specified lower filter/separator geotextile and sub-base stabilisation onto the prepared subgrade formation.
2. Install the specified sub-base and edge restraints.
3. Install the upper filter/separator geotextile on top of the sub-base.
4. Install the specified bedding layer to a uniform thickness.
5. Ensure an accurate right-angled Sudspave laying pattern by setting-out the site using pins and string-lines. Check the lines regularly for accuracy. Start installing the pre-assembled Sudspave panels (4 units/m²) by placing the webbed face downwards onto the bedding layer. Place the panels with the T-shaped lugs facing in the direction of laying on the two leading edges, with the clip-slots on the reverse-edges.
6. Progress across the site in rows by slotting panels together in a downward motion, ensuring that the 8 self-lock clips-slots engage fully with the T-shaped lugs on adjacent panels.
7. Avoid starting more than 2 new rows of panels prior to completing the row which is in progress. Avoid installing in a diagonal pattern too far ahead of completed rows. Regularly check and adjust the completed leading edge to ensure that it is straight. It is recommended that protective gloves are worn to avoid abrasions during installation.
8. Individual paver units can be separated if required. Insert the tip of a flat-blade screwdriver between each side of T-lug and the slotted paver-face in turn. Gently twist the blade to dislocate each clip-lock & lug, whilst lifting the slotted unit up and apart. Do not force clips open or pull pavers apart as this will break clips.
9. Sudspave can be cut to fit around curves or obstacles using a hand-saw or disc-saw. Using cut-pieces which do not have integral T-lugs & clips should be avoided wherever possible. However, if use of small pieces is unavoidable, these must be securely attached to adjacent panels using strong cable-ties or appropriate screws.
10. Installation of parking bay/line marker inserts is best done prior to filling cells. Push markers into the round cells until they click and lock into place. Rotate slightly to fit if required.
11. Fill the cells with the specified aggregate, so that the final level is to the top of the cells. If placing pavers and filling the cells simultaneously, it is important to keep bulk materials and vehicles away from the leading edge to avoid distortion. Do not drive vehicles on the installed panels until cells are filled with aggregate. Do not over-fill or surcharge the cells unless specified by the designer.
12. After initial settlement and trafficking, aggregate may need topping up.
13. A routine management and maintenance programme to keep the surface in good condition and free of debris and weed growth, will help to sustain the porosity, quality and longevity of the system.

NOTES

- A. Advice on subgrade CBR% strengths, ground conditions, and construction over weak ground is available from ABG.
- B. Alternative ABG stabilisation geosynthetics may be used in lieu of ABG Abgrid geogrid. These include ABG Gridtex Type 2 high-strength woven geotextile or ABG Abweb geocells. If the sub-base stabilisation is omitted, the total sub-base layer thickness ('D' on Table 1) is typically increased by a minimum of 50%.
- C. A permeable open-graded (reduced-fines) aggregate is recommended, such as DTp Type 3 low-fines roading aggregate, or BS 7533-13:2009 SuDS aggregate (4/20 or 4/40). However, where a conventional DTp Type 1 sub-base is to be used, it is essential that a drainage system such as ABG Fildrain is incorporated. Specific advice is available from ABG.
- D. Maximum sub-base particle size should match minimum sub-base thickness but must not exceed 75mm diameter. For sub-base thicknesses of around 100mm, a minimum 37.5mm particle size should be adopted to allow effective installation of the Abgrid.
- E. Typical paving edge restraint solutions include: concrete, timber, railway sleepers, steel and heavy-duty plastic.
- F. The sub-base may be overlaid by an ABG Terrex NW9 geotextile to provide enhanced water treatment function if required.
- G. To provide a stable bedding layer for Sudspave, the bedding layer must not be sand.
- H. The maximum advised gradient for vehicular trafficked applications is generally 12% (1:8) 7°. For Disabled access applications, a maximum of 8% (1:12) 5° is suggested.
- I. When designed in accordance with the recommendations, Sudspave complies with BS8300:2009 : "Design of buildings and their approaches to meet the needs of disabled people" – Code of Practice (ISBN 9780 580 57419) & Building Regulations Document 'M' Section 6.
- J. All stated dimensions & weights are nominal and in accordance with manufacturing +/- tolerances.
- K. The recommendations in this document are only suitable for use with ABG products.

Table 1: Sudspave® typical DTp Type 3 sub-base thickness (D) requirements – refer to specific construction drawing

CBR strength of subgrade soil (%) (see Table 2)	DTp Type 3 sub-base thickness (D, mm)		ABG Abgrid Geogrid
	Light vehicles only with emergency HGV access	Light vehicles with one HGV per week	
>6	100	150	20/20
4 – 6	150	200	20/20
2 – 4	175	250	30/30
1 - 2	275	375	30/30

Table 2: Field guidance for estimating sub-grade shear strengths

CBR (%)	DCP Result ¹ (Sandy Soils)	HSV Result ¹ (Clayey soils)	Tactile (Clayey soils)	Visual (Clayey or Sand Soils)
<1	<1	<30kPa	Easily indented by fingers	Adult standing will sink >30mm
1 - 2	<1	30-60kPa	Indented by strong finger/thumb pressure	Adult walking sinks 10-30mm
2 - 4	1 - 2	60-120kPa	Cannot be indented by thumb pressure	Utility truck ruts 10-25mm
5 – 7	2 - 3	120-200kPa	Can be indented by thumb nail	Loaded construction vehicle ruts by 25mm
>8	>3	>200kPa	Difficult to indent by thumb nail	Loaded construction vehicle ruts by <10mm

Note: 1. DCP results are expressed as blows per 100mm penetration. HSV results are expressed as "undrained shear strength" or C_u