



Advanced Turf

Generated on 03.05.2017

Detailed description

A high-performance grass root zone reinforcing system that allows the formation of natural grassed surfaces with the strength and durability to carry frequent vehicle traffic.

Advanced Turf System includes:

- A layer of ABG BT1 sandy loam grown turf and ABG BF1 Installation Fertiliser (35G/m²).
- A 150 or 200 mm thick layer of Advanced Turf ATS400/B Netlon Mesh Element reinforced root zone.

- Where no sub-base layer is required:

- ABG Terrex NW8 Geotextile, placed over the open-tops of any aggregate filled drainage trenches installed within the existing formation/ subgrade soil.
- A structurally sound, free-draining or pipe-drained, lightly cultivated and re-consolidated sub-grade soil formation layer.

- Additionally where a porous sub-base is required for SuDS applications:

- A layer of free-draining, open-graded sub-base such as DoT Type 1x, DoT Type 3, or a reduced-fines Type 4/40 stone or similar approved 'reduced-fines' sub-base material.
- Optional layers of Geogrid, Geotextile or Geomembrane placed on top of the subgrade formation, according to the specification requirements.

- Additionally where a non SuDS (DoT Type 1) sub-base construction is used:

- A layer of DoT Type 1 sub-base, provided with a drainage system.
- The edges of the reinforced Advanced Turf layer can be retained with concrete kerbs or timber edging, or by simply leaving a 45° battered edge to the compacted ATS root zone layer where it will abut an adjacent grassed area.
- Advanced Turf Access Routes can be delineated using kerbs, bollards, marker posts, trees or shrubs.

Features and benefits:

- Attractive, natural grass surface.
- High load bearing capacity.
- Resists rutting and compaction.
- Rapid surface drainage.
-

ABG creative geosynthetic engineering



ABG creative geosynthetic engineering

Unit E7
Meltham Mills Industrial Estate
Meltham Mills Road
Meltham
West Yorkshire
HD9 4DS

Tel: +44 (0)1484 852096

www.abgltd.com
geo@abgltd.com



Provides source control for Sustainable Drainage (SuDS).

Applications:

- Multi-use event areas.
- Emergency vehicle access roads.
- HGV access.
- Overspill car parks.
- Sports surfacing.
- Amenity areas.
- SuDS source control.

Product guidance - As Standard

Material:

Polypropylene homopolymer.

Colour:

Brown.

Size:

100 x 50 mm.

Density:

0.905–0.908 g/cm³.

Tensile strength:

3.3 kN/m (longitudinal and transverse).

Mesh/ root zone blend ratio:

5.4 kg/ 1m².

Product specification

Manufacturer

- Name: ABG creative geosynthetic engineering
- Web: www.abgltd.com
- Email: geo@abgltd.com
- Tel: +44 (0)1484 852096
- Fax: +44 (0)1484 851562
- Address: Unit E7, Meltham Mills Industrial Estate, Meltham Mills Road, Meltham, West Yorkshire HD9 4DS

Product reference Advanced Turf

[ABG creative geosynthetic engineering](#)



Sub-base layer

Required, porous
Required, DoT Type 1
Not required